

ST26 and ST28 Stereomicroscopes

Corded and Cordless Versions Available!

ST26 and 28's are full-size stereomicroscopes with small-size prices. These models feature dual-power rotating turret magnification changes and your choice of corded or LED illuminated cordless models; both with top and sub-stage illumination; with a wide base to accommodate large specimens. Cordless models include three rechargeable AA batteries and an AC adapter/recharger.

All ST26 and 28's have flexible pole-mounted designs which allow the user to rotate the entire top portion of the microscope a full 360°. This enables the user to view objects too large to fit on the stage. Heads are inclined binoculars with diopter control and interpupillary adjustment. Fine optical glass prisms in the head utilize state of the art optical coatings to reduce glare, correct color and increase contrast.

The ST26 offers 10x and 30x, while ST28's have 20x and 40x standard. Increase the magnification with optional 15x eyepieces.

Four-way lighting controls: Off, Top light only, Bottom light only, Both Top and bottom light on.



ST28 Corded Stereomicroscope

Item No.	Description
ST26	1X/3X Corded Stereomicroscope
ST26LED	1X/3X Cordless Stereomicroscope
ST28	2X/4X Corded Stereomicroscope
ST28LED	2X/4X Cordless Stereomicroscope
ST28-7001	Tungsten Bulb, 12V / 10 Watt
D1-1302	15X Widefield Eyepiece (Each)

*Actual Size: 6.5" x 4.5" x 10.5"
Shipping Dimension: 8.0" x 5.75" x 13.0"
Net Weight: 4.5 lbs
Shipping Weight: 5.5 lbs*

	ST26	ST26LED	ST28	ST28LED
Head	Binocular	Binocular	Binocular	Binocular
Eyepiece	10X WF (2)	10X WF (2)	10X WF (2)	10X WF (2)
Objectives	1X and 3X	1X and 3X	2X and 4X	2X and 4X
Condenser	None	None	None	None
Diaphragm	None	None	None	None
Stage	Plain	Plain	Plain	Plain
Illumination	Top & Bottom	Top & Bottom	Top & Bottom	Top & Bottom
Bulb	Tungsten	Rechargeable LED	Tungsten	Rechargeable LED
Focusing	Coarse	Coarse	Coarse	Coarse

Specifications

- Binocular head, inclined eye tubes
- Coated glass optics
- 3-Dimensional viewing
- Locked-on, 10X widefield eyepieces
- Diopter and interpupillary distance adjustment
- Rubber eyecups
- Rack and Pinion focus adjustment with slip clutch
- Working Distance: 71 mm

- Large base, acid and reagent resistant with locked-on stage clips
- Black/White reversible stage plate
- Frosted glass stage plate
- Non-Skid Rubber Feet, metal frame
- Dust cover and User's manual
- Limited lifetime warranty, excludes bulbs and rechargeable batteries