


PowerSpin™ PX Centrifuge

Model: C828H



- POWERSPIN™ PORTA-SPIN™ CENTRIFUGE
- FIXED SPEED 3800 RPM
- 8 PLACE FIXED ANGLE ROTOR
- 30 MIN. MECHANICAL TIMER
- 8X10ML CAPACITY WITH 18 PLACE TUBE HOLDSTER™ RACK
- POWER INPUT 15VDC



The C828 PowerSpin™ PX Centrifuge is an advanced, high-performance portable centrifuge designed to meet the demands of diverse laboratory applications. Equipped with an eight-place rotor, it is compatible with standard 2-15 ml test tubes, as well as 2 ml and 4-7.5 ml tubes when used with optional adapters. This versatility makes it ideal for handling a variety of sample sizes in clinical, research, and industrial settings. Designed for 12V DC operation, it includes a vehicle power adapter (car adapter) for convenient use in remote locations, on-site testing, or mobile laboratories. This centrifuge offers variable speed control, allowing you to adjust the speed according to your specific sample processing needs. It features a 8-place rotor, accommodating up to eight tubes for efficient sample separation. The dual lid lock ensures enhanced safety by securely locking the lid in place during operation, while the built-in leveling system provides stability even on uneven surfaces, ensuring consistent performance. With the C827 PXV, you can count on reliable and efficient centrifugation wherever you go, combining convenience and performance for a wide range of applications.



ADDITIONAL INFORMATION

TOP SELECTION	No	
ACCESSORIES	Accessories (Sold Separately)	
	C800-00	8 Place Rotor
	C800-01	8 Place Rotor
	C800-75	Tachometer, Laser Digital with Reflective Tape, Batteries, In A Storage Case
	C800-02	Regular tube shield, pack of 2
	C800-03	Adapter for short tubes, pack of 10
	C800-04	Pediatric or microtube adapter, pack of 2
	C800-05	Tube Lift Adapters, Pk/12
	C800-12	Balance Tube Holdster
	C826-06	Porta-Spin 12 VDC Adapter, Plugs in to Car Charger, Replacement
	C826-12	Porta-Spin Ac Adapter, 110 Volt, USA Power Cord
SPECIFICATION	Number of Tubes	8
	Tube Capacity	2-15 ml
	Blood	Yes
	Specimens Fecal	Not recommended
	Urine	Not recommended
	Microhematocrit	Not recommended
	Speed	Fixed
	Rotor	Fixed Angle
	Maximum RPM	3800
	Maximum RCF(g)	1320
SIZE AND WEIGHT	Size	10.2 in x 11.8 in x 7.9 in
	Shipping Size	13.4 in x 14.8 in x 10.6 in



	<div><div>Weight</div><div>Shipping Weight</div></div>	<div><div>18 lbs</div><div>19 lbs</div></div>
<div>WARRANTY</div>		<div>1 years</div>

